



## COMMITTED TO DELIVERING HIGH-QUALITY, INNOVATIVE PRODUCTS AND UNRIVALED CUSTOMER SERVICE.

Lippert™ is a leading, global manufacturer and supplier of highly engineered products and customized solutions, dedicated to shaping, growing, and bettering the RV, marine, automotive, commercial vehicle and building products industries. We combine our strategic manufacturing capabilities with the power of our winning team culture to deliver unrivaled Customer Service, award-winning Innovation, and premium Products to every customer we do business with.

COMMITTED TO DELIVERING  
CUSTOMIZED SOLUTIONS

EXTENSIVE MANUFACTURING  
CAPABILITIES

FIRST-CLASS CUSTOMER  
SERVICE

SERVE A MULTITUDE OF  
INDUSTRIES GLOBALLY

LIPPERT COMPONENTS, INC #148 1205 E LINCOLN ST NAPPANEE, IN 46550-2240 USA AR@lci1.com

### Square Baggage Doors

400 Core: 1.5"; Outer: 1.375" - Outside Mount

401 Core: 1.5"; Outer: 1.375" - Outside Mount

410 Core: 1.5"; Outer: 1.375" - Inside Mount

Minimum - 9" Width or Height  
Maximum - Width 96" & Height 78"  
TH/BH width > 96" & height > 48"  
LH/RH width > 48" & height > 96"

|       |                |            |
|-------|----------------|------------|
| Date: | Customer Name: | Sales Rep: |
|-------|----------------|------------|

#### Write Similar Part Number Below and Select Changes:

If it is a new door, please reference the entire sheet below.

|                  |                                 |                                           |              |                                |
|------------------|---------------------------------|-------------------------------------------|--------------|--------------------------------|
| Application Type | Which series?                   | Rough Opening Size - to the nearest 1/16" | Frame Color* | Additional Door Configurations |
| Baggage (BAG)    | 400 - 0.065 Extrusion Thickness | Width -                                   | White (WH)   | Welded Bottom (SD)             |
| Generator (GEN)  | 401 - 0.090 Extrusion Thickness | Height -                                  | Black (BK)   | 3-Sided Frame (3SF)            |
|                  | 410                             |                                           | Mill (ML)    | -No bottom extrusion           |
|                  |                                 |                                           |              | Double Door (DD)               |

|                                     |                                      |                     |                                      |                     |
|-------------------------------------|--------------------------------------|---------------------|--------------------------------------|---------------------|
| Who is supplying the skin material? | Exterior Skin Material               | Exterior Skin Color | Interior Skin Material               | Interior Skin Color |
| Lippert/Challenger                  | Aluminum                             |                     | Aluminum                             |                     |
| Customer Supplied (CS)              | Fiberglass                           |                     | Fiberglass                           |                     |
| -Interior                           | Gel Coat (fiberglass with substrate) |                     | Gel Coat (fiberglass with substrate) |                     |
| -Exterior                           |                                      |                     | Plastic                              |                     |
| -Interior & exterior                |                                      |                     |                                      |                     |
| U-Skin/Plain                        |                                      |                     |                                      |                     |

|            |                                       |                             |                             |                          |
|------------|---------------------------------------|-----------------------------|-----------------------------|--------------------------|
| Door Type  | Hinge Type                            | Hinge Location              | Strut/Bracket: LH, RH, & TH | Degree for Strut/Bracket |
| Tube (TB)  | Stacked (H-STAK)                      | LH/RH width ≠ 2x the height | Cable: BH                   | Standard is 90 Degrees   |
| Vapor (VP) | 3-Part (H3AL-00)                      | Top (TH)                    | None                        | 85 (A)                   |
|            | 5-Part-Aluminum (HSAL)                | Bottom (BH)                 | Strut                       | 90 (C)                   |
|            | Continuous-Aluminum (H-Con AL)        | Left (LH)                   | -Installed (GSTI)           | 95 (D)                   |
|            | Continuous-Stainless Steel (H-Con SS) | Right (RH)                  | -Ship loose (GSTS)          | 100 (E)                  |
|            |                                       |                             | Bracket (BKT)               | 110 (F)                  |
|            |                                       |                             | 2 Cable (CBL)               | 115 (H)                  |
|            |                                       |                             |                             | 120 (J)                  |
|            |                                       |                             |                             | 130 (K)                  |
|            |                                       |                             |                             | 135 (L)                  |
|            |                                       |                             |                             | 150 (M)                  |

|                     |                                                      |                             |             |                           |
|---------------------|------------------------------------------------------|-----------------------------|-------------|---------------------------|
| Seal on Outer Frame | Lock Brand                                           | Trim Ring Style             | Gutter Trim | Screw Cover - 401 Only    |
| Yes                 | *See Guide for Details & Specify in Comments Section | None                        | Yes         | *Plastic = Black or White |
| No                  | Yes                                                  | Short - < 2" Wall Thickness | No          | None                      |
|                     | Route Out Only                                       | Long - ≥ 2" Wall Thickness  |             | Aluminum                  |
|                     | No Latch & No Route Out                              |                             |             | Plastic*                  |

#### GEN Door only - No DD

|               |                     |            |                         |                      |
|---------------|---------------------|------------|-------------------------|----------------------|
| Vent Type     | Vent Size           | Mesh Count | Mesh/Louver Orientation | Mesh/Louver Location |
| Mesh          | 10 x 10 (Mesh Only) | 1          | Horizontal              | Center               |
| Louver        | 4 x 12              | 2          | Vertical                | Left                 |
| Mesh & Louver | 4 x 24*             |            |                         | Right                |
|               |                     |            |                         | Top (Mesh Only)      |
|               |                     |            |                         | Bottom (Mesh Only)   |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| Notes:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Comments: |
| <p>*Latch QTY determined by door size<br/>1 latch: &lt; 24"<br/>2 K/T or 1 slam: 24 - 48"<br/>3 K/T or 2 latches: &gt; 48"</p> <p>*Standard latch locations<br/>2 K/T: key on left for TH/BH &amp; bottom for LH/RH doors<br/>1K/2T: key installed in the center</p> <p>*Strut for heights between 14-48"</p> <p>*Frame, hinge, trim ring, and screw cover will all be the same color if applicable.</p> <p>*4 x 24 vent LH/RH GEN door with K/T minimum W x H ≥ 32.375 x 8.938<br/>*4 x 24 vent TH/BH GEN door with K/T minimum W x H ≥ 8.938 x 32.375</p> |           |